

LISA2-RS-PIN

~19° spot beam. 6.8 mm high variant with location pin installation.

SPECIFICATION:

Dimensions	Ã~ 9.9 mm
Height	6.8 mm
Fastening	glue, pin
ROHS compliant	yes ⓘ




MATERIALS:

Component	Type	Material	Colour	Finish	Length
LISA2-RS	Single lens	PMMA	clear		9.9
LISA2-HLD-PIN	Holder	PC	black		9.9

ORDERING INFORMATION:



Component		Qty in box	MOQ	MPQ	Box weight (kg)
FP11055_LISA2-RS-PIN	Single lens	2000	300	100	1.4
» Box size: 310 x 230 x 60 mm					



OPTICAL RESULTS (MEASURED):




LED XD16
FWHM / FWTM 15.0° / 42.0°
Efficiency 70 %
Peak intensity 4.2 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files




LED XP-G
FWHM / FWTM 24.0°
Efficiency 90 %
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files



LED XQ-E HI
FWHM / FWTM 11.0° / 27.0°
Efficiency 86 %
Peak intensity 11.5 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:




Light distribution files

OPTICAL RESULTS (MEASURED):





LED LUXEON Z ES
 FWHM / FWTM 15.0° / 38.0°
 Efficiency 84 %
 Peak intensity 6.6 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files



LED NCSxE17A
 FWHM / FWTM 13.0° / 43.0°
 Efficiency 72 %
 Peak intensity 4.3 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files




LED SFH 4180S
 FWHM / FWTM 9.0° / 24.0°
 Efficiency %
 LEDs/each optic 1
 Light colour/type IR
 Required components:

Light distribution files

OPTICAL RESULTS (MEASURED):

SAMSUNG

LED LH181B
FWHM / FWTM 16.0° / 50.0°
Efficiency 71 %
Peak intensity 3.1 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files

SHARP


LED Double Dome (GM2BB)
FWHM / FWTM 18.0°
Efficiency 90 %
LEDs/each optic 1
Light colour/type White
Required components:

Light distribution files


OPTICAL RESULTS (SIMULATED):



LED CSP 2323 (BXCP)
 FWHM / FWTM 16.0° / 44.0°
 Efficiency 77 %
 Peak intensity 4.1 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:




LED XQ-A
 FWHM / FWTM 10.0° / 20.0°
 Efficiency 90 %
 Peak intensity 21.5 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files



LED XQ-E HD
 FWHM / FWTM 14.5° / 28.5°
 Efficiency 91 %
 Peak intensity 10.1 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):




LED LUXEON IR 2720
 FWHM / FWTM 14.0° / 34.0°
 Efficiency 88 %
 LEDs/each optic 1
 Light colour/type IR
 Required components:



Light distribution files





LED LUXEON Z ES
 FWHM / FWTM 16.0° / 34.0°
 Efficiency 91 %
 Peak intensity 7.9 cd/lm
 LEDs/each optic 1
 Light colour/type White
 Required components:



Light distribution files



LED SST-10-IR-B90
 FWHM / FWTM 18.0° / 40.0°
 Efficiency 89 %
 LEDs/each optic 1
 Light colour/type IR
 Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):

OSRAM
Opto Semiconductors


LED OSLON Black Flat (LUW HWQP)
FWHM / FWTM 12.0° / 28.0°
Efficiency 89 %
Peak intensity 11.4 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files


OSRAM
Opto Semiconductors

LED OSLON Pure 1414
FWHM / FWTM 14.0 + 13.0° / 26.0°
Efficiency 93 %
Peak intensity 12.7 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:



OSRAM
Opto Semiconductors

LED OSLON Square EC
FWHM / FWTM 18.0° / 40.0°
Efficiency 90 %
Peak intensity 5.6 cd/lm
LEDs/each optic 1
Light colour/type White
Required components:




Light distribution files

OPTICAL RESULTS (SIMULATED):

OSRAM
Opto Semiconductors


LED OSLON SSL 150
FWHM / FWTM 16.0° / 32.0°
Efficiency 92 %
Peak intensity 9 cd/Im
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files

OSRAM
Opto Semiconductors


LED OSLON SSL 80
FWHM / FWTM 16.0° / 35.0°
Efficiency 90 %
Peak intensity 7.5 cd/Im
LEDs/each optic 1
Light colour/type White
Required components:



Light distribution files

OSRAM
Opto Semiconductors

LED SFH 4170S
FWHM / FWTM 10.0° / 22.0°
Efficiency 77 %
LEDs/each optic 1
Light colour/type IR
Required components:





Light distribution files

OPTICAL RESULTS (SIMULATED):

OSRAM
Opto Semiconductors

LED SFH 4770S
FWHM / FWTM 13.0° / 31.0°
Efficiency 88 %
LEDs/each optic 1
Light colour/type IR
Required components:



Light distribution files

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Poznan, Poland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)